

# Data Sheet Cross-Bracing

Release date : 12.06.2010

Product range : 24" - 120"

Product code : CB

Commodity / HS code : 73269098

Elskensakker 8, NL-5571 SK  
Bergeijk, The Netherlands

Tel +31 497 542527

Fax +31 497 555399

Email info@dhatec.nl

Web www.dhatec.nl

## Application:

The Cross-Bracing ensures stabilization against ovality of large diameter pipes in combination with small wall thicknesses.

## 5 reasons to choose this product:

- Easy to apply
- Reusable
- Strong clamping, without tensioning wire
- No difficulties with diameter tolerances
- Suitable for use in combination with a bevel protector and plastic plug for stabilization, bevel protection and pipe closure at the same time.



Fig 1: Cross-Bracing in pipe

## Material qualities:

Bracing legs: Steel : 37-2 (Mat. nr: 1.0037) 35x35x3 mm

Support feet: Steel : 37-2 with Rubber cover

Nuts: M 27



Fig 2: Support feet of Cross-Bracing

## Function:

The Cross-Bracing is defolded and positioned inside the pipe-end in a 90°-angle. The nuts are tightened with a torque wrench, which forces the Cross-Bracing to expand against the pipe wall.

## Additional information:

- Different models available, also for internal bracing
- Torque wrench available for constant fastening
- Supplied in the exact size and ready to use



Fig 3: Cross-Bracings in pipes